

# Technical Specifications

## TDW 4240

Measuring range	<ul style="list-style-type: none"><li>▪ R: 0.10 to 8.00 m<sup>2</sup>·K/W</li><li>▪ U: 0.12 to 3.70 W/(m<sup>2</sup>·K)</li></ul>
Sample dimensions – window (H x W)	<ul style="list-style-type: none"><li>▪ Variant A: 1480 mm x 1230 mm</li><li>▪ Variant B: 2180 mm x 1480 mm</li></ul>
Sample dimensions – door (H x W)	<ul style="list-style-type: none"><li>▪ Variant A: 2180 mm x 1230 mm</li><li>▪ Variant B: 2180 mm x 2000 mm</li></ul>
Specimen thickness (D)	Up to 560 mm
Temperature range	<ul style="list-style-type: none"><li>▪ Cold section: -15°C to 40°C</li><li>▪ Warm section: +10°C to 60°C</li></ul>
Interface	1x RS 232, 1x Gigabit Ethernet
Dimensions (H x W x D)	<ul style="list-style-type: none"><li>▪ Closed: 400 cm x 400 cm x 405 cm</li><li>▪ Open: 400 cm x 610 cm x 405 cm</li></ul>
Power supply	230 V/400 V/50 Hz
Weight	4680 kg